

SICCO Vacuum-Desiccator, Bohlender

Solid walls of 25 mm thickness, circular silicone gasket, vacuum gauge, V 1880-04 including two shelves, usable with up to three shelves, V 1880-08 including three shelves, usable with up to five shelves, and V 1880-12 including four shelves, usable with up to seven shelves.

- Clear acrylic panels, interior is visible from all sides
- Circular silicone seal
- Non slip rubber feet
- Variable height shelves
- Vacuum gauge (0-760 mm of mercury)
- Vacuum up to 0,0001 Torr
- Two needle valves with O.D. 9,0 mm

SICCO Vacuum Desiccators are suitable for storing sensitive products in a vacuum. The vacuum inside the desiccator ensures rapid drying of the stored products. These systems allow storage in an oxygen and carbon dioxide free environment and are, for example, suitable for storage of semiconductor samples.

Technical data:

Panels:	clear
Material:	PMMA
Temperature resistance:	from -20°C to +70°C
Use:	vacuum up to 0,0001 Torr
Stand:	rubber feet
Excess length of valves and vacuum gauge:	100 mm
Maximum all-over load per shelf:	9 kg

Outer dimensions W x H x D	Usable interior space W x H x D	Useful volume l	Total volume l	Weight kg	Load capacity max. kg	Order No.
mm	mm					
300x340x300	260x260x260	17.5	17.5	15	30	10 17 68804
300x440x300	260x360x260	24.5	24.5	18	40	10 17 68808
315x550x310	265x460x260	31.5	31.5	27	50	10 17 68812

